4A0-106

Alcatel-Lucent
Alcatel-Lucent Virtual Private Routed Networks

OfficialCerts.com is a reputable IT certification examination guide, study guides and audio exam provider. We ensure that you pass your 4A0-106 exam in first attempt and also get high scores to acquire Alcatel-Lucent certification.

If you use OfficialCerts 4A0-106 Certification questions and answers, you will experience actual 4A0-106 exam questions/answers. We know exactly what is needed and have all the exam preparation material required to pass the exam. Our Alcatel-Lucent exam prep covers over 95% of the questions and answers that may be appeared in your 4A0-106 exam. Every point from pass4sure 4A0-106 PDF, 4A0-106 review will help you take Alcatel-Lucent 4A0-106 exam much easier and become Alcatel-Lucent certified.

Here's what you can expect from the OfficialCerts Alcatel-Lucent 4A0-106 course:

* Up-to-Date Alcatel-Lucent 4A0-106 questions as experienced in the real exam.
* 100% correct Alcatel-Lucent 4A0-106 answers you simply can't find in other 4A0-106 courses.
* All of our tests are easy to download. Your file will be saved as a 4A0-106 PDF.
* Alcatel-Lucent 4A0-106 brain dump free content featuring the real 4A0-106 test questions.

Alcatel-Lucent 4A0-106 certification exam is of core importance both in your Professional life and Alcatel-Lucent certification path. With Alcatel-Lucent certification you can get a good job easily in the market and get on your path for success. Professionals who passed Alcatel-Lucent 4A0-106 exam training are an absolute favorite in the industry. You will pass Alcatel-Lucent 4A0-106 certification test and career opportunities will be open for you.

http://www.officialcerts.com/exams.asp?examcode=4A0-106

Question: 1
In a VPRN the PE device is configured to run which of the following protocols? (Choose three.)

A. MP-BGP for exchanging customer routes with other PEs
B. A routing protocol for exchanging customer routes with the CE
C. MPLS for exchanging labels with other provider core devices
D. MPLS for exchanging labels with the CE devices
E. Targeted LDP for exchanging VPRN labels with other PE devices
F. A label signaling protocol for defining transport tunnels between PE and CE devices

Answer: A, B, C

Question: 2
Choose the answer that best completes the following sentence. The CE device is typically configured with _____.

A. A single routing protocol for exchanging routes with both the internal customer routers and with the PE
B. MP-BGP to exchange routes with the PE.
C. MPLS and a routing protocol for the exchange of labels and routes with the PE
D. MPLS for exchanging labels with other CE devices
E. A routing protocol for exchanging routes with the internal customer routers and a routing protocol for exchanging routes with the PE

Answer: E

Question: 3
Which of the following terms also correctly describes a Layer 3 VPN? (Choose three)

A. VPRN
B. BGP/MPLS VPN
C. VLL
D. VPLS
E. IP-VPN
F. ePipe

Answer: A, B, E

Question: 4
What are the main functions of a Layer 3 VPN? (Choose three).

A. Distributing customer routing information between sites
B. Forwarding customer data packets
C. Providing an integrated billing solution
D. Maintaining separation between distinct customer networks
E. Allowing the implementation of Layer 3 devices in the provider core

Answer: A, B, D

Question: 5
Which of the following statements are true regarding P devices in an MPLS VPRN? (Choose two.)

A. Participate in service provider core routing
B. P devices are not required to be MPLS enabled. MPLS is only required on the PE devices

C. Run a common routing protocol with the CE router
D. Must support MP-BGP
E. Do not have any connections to the CE
F. Must be aware of the VPRNs

Answer: A, E

Question: 6
What are the two primary problems the service provider must consider when providing traditional Layer 3 VPN services using only a single common routing table in the provider core? (Choose two)

A. Memory exhaustion in the provider core
B. Route leaking between the customer networks
C. CPU utilization for route processing
D. Unwanted packet forwarding between customer networks

Answer: B, D

Question: 7
When a Service Provider offers VPRN services to its customers, which of the following functions are expected to be the responsibility of the Service Provider? (Choose three)

A. Distributing the customer generated labels between sites
B. Distributing the customer routing information between sitesDistributing the customer? routing information between sites
C. Forwarding the customer originated data packets to the appropriate destination
D. Forwarding the provider originated data packets to the appropriate customer site
E. Providing secure layer 3 routing exchange between sites

Answer: B, C, E

Question: 8
In a traditional layer 3 VPN which of the following will be an issue when there is overlapping address space between two customers? Choose the best answer.

A. There will be increased memory usage on the PE
B. There will be increased CPU utilization on the PE
C. The CE will reject the overlapping prefix
D. The PE will not recognize the prefixes as being different
E. There is no issue with overlapping address space in a traditional Layer 3 VPN

Answer: D

Question: 9
Complete the following statement. In a VPRN, the label signaled by RSVP-TE is used to
_____.

A. Identify the egress PE in the MPLS domain
B. Signal the egress VPRN ID
C. Identify the ingress PE in the MPLS domain
D. Transport route updates between PEs

Answer: A