

642-432

Cisco

Cisco Voice Over IP

Visit: <http://www.pass4sureofficial.com/exams.asp?examcode=642-432>

Pass4sureofficial.com is a reputable IT certification examination guide, study guides and audio exam provider, we not only ensure that you pass your 642-432 exam in first attempt, but also you can get a high score to acquire Cisco certification.

If you use pass4sureofficial 642-432 Certification questions and answers, you will experience actual 642-432 exam questions/answers. We know exactly what is needed and have all the exam preparation material required to pass the exam. Our Cisco exam prep covers over 95% of the questions and answers that may be appeared in your 642-432 exam. Every point from pass4sure 642-432 PDF, 642-432 review will help you take Cisco 642-432 exam much easier and become Cisco certified. All the Questions/Answers are taken from real exams.

Here's what you can expect from the Pass4sureOfficial Cisco 642-432 course:

- * Up-to-Date Cisco 642-432 questions taken from the real exam.
- * 100% correct Cisco 642-432 answers you simply can't find in other 642-432 courses.
- * All of our tests are easy to download. Your file will be saved as a 642-432 PDF.
- * Cisco 642-432 brain dump free content featuring the real 642-432 test questions.

Cisco 642-432 certification exam is of core importance both in your Professional life and Cisco certification path. With Cisco certification you can get a good job easily in the market and get on your path for success. Professionals who passed Cisco 642-432 exam training are an absolute favorite in the industry. You will pass Cisco 642-432 certification test and career opportunities will be open for you.



QUESTION 1:

Which type of signaling is DTMF?

- A. Supervisory
- B. Route
- C. Informational
- D. Address

Answer: D

Explanation:

Start dial supervision is the line protocol that defines how the equipment seizes the E&M trunk and passes the address signaling information such as dual tone multifrequency (DTMF) digits.

Address Signaling

Address signaling typically represents the digits dialed (called party's number). There are two options used to pass address information. Either Pulse dial (rotary dialing) or Tone dial (DTMF) can be used. The default for Cisco routers and gateways is DTMF.

QUESTION 2:

You have set up a complex dial plan using translation rules. The following translation rule has been configured.

What output would correspond to the test translation-rule command?

```
translation-rule 1
rule 0 ^0.. 215550210
rule 1 ^1.. 215550211
rule 2 ^2.. 215550212
rule 3 ^3.. 215550213
rule 4 ^4.. 215550214
rule 5 ^5.. 215550215
rule 6 ^6.. 215550216
rule 7 ^7.. 215550217
rule 8 ^8.. 215550218
rule 9 ^9.. 215550210
```

- A. test translation-rule 1512
The replaced number: 21555021512
- B. test translation-rule 1555
The replaced number: 55521555021
- C. test translation-rule 1617
The replaced number: 61721555021
- D. test translation-rule 1910
The replaced number: 21555021910

Answer: A

Explanation:

New Delhi(2-digit indial range)

!-- Only relevant "IOS translation rule" output is presented

!

translation-rule 1

!-- The "1" above is the tag for the set.

rule 0 ^0. 1011000

rule 1 ^1. 1011001

rule 2 ^2. 1011002

rule 3 ^3. 1011003

rule 4 ^4. 1011004

rule 5 ^5. 1011005

rule 6 ^6. 1011006

rule 7 ^7. 1011007

rule 8 ^8. 1011008

rule 9 ^9. 1011009

!

!-- These rules replace the first digit of a 2-digit number with the corresponding
!-- translation. The router looks for a 2-digit number starting with a leading [0-9].

!-- The caret, "^" ensures the match only happens at the start of the digit string

!-- rather than any occurrence in a digit string. This ensures the router makes the
!-- translation only for the leading digits. By default, if an explicit match is made

!-- on a digit (in this case the first digit) the router replaces it with the new

!-- digits. Therefore, to keep the original numbering, the matched digit needs to be

!-- replaced with the same digit at the end of the modified string. Once the call

!-- comes in, the called number prepended with 101100 followed by the

!-- original 2 digits.

!

voice-port 1/0:1

translate called 1

cptone IN

comand-type a-law

!

!-- The translation rule is applied to the voice port where the

!-- call comes in to the router. When a call comes in from the

!-- telephone network towards the router, the called number

!-- is translated before it is matched on any dial peers.

!

dial-peer voice 100 voip

destination-pattern 101100..

session target ipv4:main site IP address

ip precedence 5

dtmf-relay h245-alphanumeric

!

!-- The VoIP dial peer needs to be configured to match on the new numbering plan
This output was captured from the NewDelhi router which shows the translation rules applied while dialing from the NewDelhi site.

NewDelhi- Output

!-- It is possible to confirm the translation rules are working:!!NewDelhi#test
translation-rule 1 99!-- Original called number is "99"The replaced number:
10110099!-- Translated to 8 digits

QUESTION 3:

What is the optimal end-to-end delay that should be achieved in a VoIP network?

- A. 20 ms
- B. 100 ms
- C. 150 ms
- D. 400 ms

Answer: C

Explanation:

Delay Specifications

Range in Milliseconds	Description
0-150	Acceptable for most user applications.
150-400	Acceptable provided that administrators are aware of the transmission time and it's impact on the transmission quality of user applications.
Above 400	Unacceptable for general network planning purposes, however, it is recognized that in some exceptional cases this limit will be exceeded.

QUESTION 4:

Which three are supervisory signals? (Choose three)

- A. busy
- B. on hook
- C. off hook
- D. call waiting

E. ring

Answer: B, C, E

Explanation:

1. Supervisory Signalling - electrical voltages and tones that can be heard are used to signify call status as follows:
 2. 1. On-hook - produces an open circuit which does not allow any signalling, only the ringer can operate.
 2. Off-hook - lifting the handset closes the circuit and allows the telephone switch to send an audible dial tone to the receiver.
 3. Ringing - the switch sends a ringing voltage to the destination telephone as notification of an incoming call. Also an audible ringing tone is sent to the caller telephone to indicate that the call is progressing. This tone takes the form of a pattern called Cadence In Europe this Cadence takes the form of a double ring (duration of 0.4s separated by 0.2s) followed by two seconds of silence, whereas in the US it takes the form of two seconds of ring followed by four seconds of silence.
-

QUESTION 5:

What is the E.164 numbering plan?

- A. A proprietary PBX number plan.
- B. The IETF North American number plan.
- C. The European PBX standard telephony number plan.
- D. The ITU worldwide number plan.

Answer: D

Explanation:

Numbering Scheme

The standard PSTN is a large, circuit-switched network. It uses a specific numbering scheme, which complies with the ITU-T international public telecommunications numbering plan (E.164) recommendations. For example, in North America, the North American Numbering Plan (NANP) is used, which consists of an area code, an office code, and a station code. Area codes are assigned geographically, office codes are assigned to specific switches, and station codes identify a specific port on that switch.

The format in

North America is 1Nxx-Nxx-xxxx, with N = digits 2 through 9 and x = digits 0 through 9.

Internationally, each country is assigned a one- to three-digit country code; the country's dialing plan follows the country code. In Cisco's voice implementations, numbering schemes are configured using the destination-pattern command.

E.164 is an ITU-T recommendation which defines the international public telecommunication numbering plan used in the PSTN and some other data networks.

Pass4SureOfficial.com Lifetime Membership Features;

- Pass4SureOfficial Lifetime Membership Package includes over **2500** Exams.
- **All** exams Questions and Answers are included in package.
- **All** Audio Guides are included **free** in package.
- **All** Study Guides are included **free** in package.
- **Lifetime** login access.
- Unlimited download, no account expiry, no hidden charges, just one time \$99 payment.
- **Free updates** for Lifetime.
- **Free Download Access** to All new exams added in future.
- Accurate answers with explanations (If applicable).
- Verified answers researched by industry experts.
- Study Material **updated** on regular basis.
- Questions, Answers and Study Guides are downloadable in **PDF** format.
- Audio Exams are downloadable in **MP3** format.
- **No authorization** code required to open exam.
- **Portable** anywhere.
- 100% success **Guarantee**.
- **Fast**, helpful support 24x7.

View list of All exams (Q&A) downloads

<http://www.pass4sureofficial.com/allexams.asp>

View list of All Study Guides (SG) downloads

<http://www.pass4sureofficial.com/study-guides.asp>

View list of All Audio Exams (AE) downloads

<http://www.pass4sureofficial.com/audio-exams.asp>

Download All Exams Samples

<http://www.pass4sureofficial.com/samples.asp>

To purchase \$99 Lifetime Full Access Membership click here

<http://www.pass4sureofficial.com/purchase.asp>

3COM	CompTIA	Filemaker	IBM	LPI	OMG	Sun
ADOBE	ComputerAssociates	Fortinet	IISFA	McAfee	Oracle	Sybase
APC	CWNP	Foundry	Intel	McData	PMI	Symantec
Apple	DELL	Fujitsu	ISACA	Microsoft	Polycom	TeraData
BEA	ECCouncil	GuidanceSoftware	ISC2	Mile2	RedHat	TIA
BICSI	EMC	HDI	ISEB	NetworkAppliance	Sair	Tibco
CheckPoint	Enterasys	Hitachi	ISM	Network-General	SASInstitute	TruSecure
Cisco	ExamExpress	HP	Juniper	Nokia	SCP	Veritas
Citrix	Exin	Huawei	Legato	Nortel	See-Beyond	Vmware
CIW	ExtremeNetworks	Hyperion	Lotus	Novell	SNIA	

